

Appl. Serial No. 09/966,049
Amendment Dated November 11, 2005
Reply to Office Action of July 25, 2005

31876-0263

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1 (Currently Amended)

A grid that monitors a design simulation to support design verification coverage analysis, comprising:

a monitor declaration that provides a unique name for the grid;

n ordered axis declarations wherein n is at least 1, each said axis declaration names an axis comprising a first axis through a nth axis, wherein each said axis corresponds to a functional attribute of the design and has an axis size that comprises two or more functional states of said functional attribute and has a corresponding axis variable;

one or more logic expressions that evaluate whether the design has achieved one or more of said functional states, said logic expressions set each one of said n axis variables to an integer value corresponding to said functional state when said logic expressions evaluate true; and

a grid declaration that converts said n axis variables to an integer that is a unique linear index value that corresponds to the cross-product of said functional states achieved by the design, said grid declaration also records a hit at said unique linear index value.

Claim 2 (Canceled)

Appl. Serial No. 09/966,049
Amendment Dated November 11, 2005
Reply to Office Action of July 25, 2005

31876-0263

Claim 3 (Currently Amended)

A method that makes a grid that monitors a design simulation to support design verification coverage analysis, comprising:

providing a monitor declaration that provides a unique name for the grid;

providing n ordered axis declarations wherein n is at least 1, each said axis declaration names an axis comprising a first axis through a n th axis, wherein each said axis corresponds to a functional attribute of the design and has an axis size that comprises two or more functional states of said functional attribute and has a corresponding axis variable;

providing one or more logic expressions that evaluate whether the design has achieved one or more of said functional states, said logic expressions set each one of said n axis variables to an integer value corresponding to said functional state when said logic expressions evaluate true; and

providing a grid declaration that converts said n axis variables to an integer that is a unique linear index value that corresponds to the cross-product of said functional states achieved by the design, said grid declaration also records a hit at said unique linear index value.

Claim 4 (Currently Amended)

A method that monitors a design simulation using a grid to support design verification coverage analysis, comprising:

Appl. Serial No. 09/966,049
Amendment Dated November 11, 2005
Reply to Office Action of July 25, 2005

31876-0263

declaring a monitor in a monitor declaration that provides a unique name for the grid;

declaring n ordered axes using axis declarations, wherein n is at least 1, each said axis declaration names an axis comprising a first axis through a nth axis, wherein each said axis corresponds to a functional attribute of the design and has an axis size that comprises two or more functional states of said functional attribute and has a corresponding axis variable;

evaluating one or more logic expressions to determine whether the design has achieved one or more of said functional states;

setting each one of said n axis variables to an integer value corresponding to said functional state when said logic expressions evaluate true; and

using a grid declaration to convert said n axis variables to an integer that is a unique linear index value that corresponds to the cross-product of said functional states achieved by the design and to record a hit at said unique linear index value.

Claim 5 (Currently Amended)

A program storage device readable by a machine, tangibly embodying a program of instructions executable by the machine to perform a method that monitors a design simulation using a grid to support design verification coverage analysis, comprising:

declaring a monitor in a monitor declaration that provides a unique name for the grid;

Appl. Serial No. 09/966,049
Amendment Dated November 11, 2005
Reply to Office Action of July 25, 2005

31876-0263

declaring n ordered axes using axis declarations, wherein n is at least 1, each said axis declaration names an axis comprising a first axis through a nth axis, wherein each said axis corresponds to a functional attribute of the design and has an axis size that comprises two or more functional states of said functional attribute and has a corresponding axis variable;

evaluating one or more logic expressions to determine whether the design has achieved one or more of said functional states;

setting each one of said n axis variables to an integer value corresponding to said functional state when said logic expressions evaluate true; and

using a grid declaration to convert said n axis variables to an integer that is a unique linear index value that corresponds to the cross-product of said functional states achieved by the design and to record a hit at said unique linear index value.

Claim 6 (Currently Amended)

A ~~dependent~~ claim according to Claim 1, ~~2~~, 3, 4 or 5 wherein said grid declaration maintains a map of hits at each linear index value determined during a simulation, and downloads said map to a database.

Claim 7 (Currently Amended)

A ~~dependent~~ claim according to Claim 1, ~~2~~, 3, 4 or 5 wherein said unique linear index value is determined by multiplying the integer value of each said axis variable except the nth said axis variable by the product of the sizes of each higher-order axis

Appl. Serial No. 09/966,049
Amendment Dated November 11, 2005
Reply to Office Action of July 25, 2005

31876-0263

than the axis to which said axis variable corresponds, summing the results, and adding the integer value of the nth said axis variable.

Claim 8 (Currently Amended)

A ~~dependent~~ claim according to Claim 1, ~~2~~-3, 4 or 5, wherein said monitor declaration, said axis declarations, said logic expressions, and said grid declaration are translated into a computer program comprising a higher-order software language using a parser, wherein said parser further translates each said unique linear index value to a character string comprising a concatenation of character strings that correlate to said grid name and to each said functional state within said cross-product achieved by the design.

Claim 9 (Canceled)

Claim 10 (Currently Amended)

A grid that monitors a design simulation to support design verification coverage analysis, comprising:

a monitor declaration that provides a unique name for the grid;

n ordered axis declarations wherein n is at least 1, each said axis declaration names an axis comprising a first axis through a nth axis, wherein each said axis corresponds to a functional attribute of the design and has an axis size that comprises two or more functional states of said functional attribute and has a corresponding axis variable;

Appl. Serial No. 09/966,049
Amendment Dated November 11, 2005
Reply to Office Action of July 25, 2005

31876-0263

one or more logic expressions that evaluate whether the design has achieved one or more of said functional states, said logic expressions set each one of said n axis variables to an integer value corresponding to said functional state when said logic expressions evaluate true;

a grid declaration that converts said n axis variables to an integer that is a unique linear index value that corresponds to the cross-product of said functional states achieved by the design by multiplying the integer value of each said axis variable except the nth said axis variable by the product of the sizes of each higher-order axis than the axis to which said axis variable corresponds, summing the results, and adding the integer value of the nth said axis variable, said grid declaration also records a hit and maintains a map of hits at each linear index value determined during a simulation, and downloads said map to a database; and

a parser that translates said monitor declaration, said axis declarations, said logic expressions, and said grid declaration into a computer program comprising a higher-order software language, said parser further translates each said unique linear index value to a character string comprising a concatenation of character strings that correlate to said grid name and to each said functional state within said cross-product achieved by the design.

Claim 11 (Canceled)

Appl. Serial No. 09/966,049
Amendment Dated November 11, 2005
Reply to Office Action of July 25, 2005

31876-0263

Claim 12 (Currently Amended)

A method that makes a grid that monitors a design simulation to support design verification coverage analysis, comprising:

providing a monitor declaration that provides a unique name for the grid;

providing n ordered axis declarations wherein n is at least 1, each said axis declaration names an axis comprising a first axis through a nth axis, wherein each said axis corresponds to a functional attribute of the design and has an axis size that comprises two or more functional states of said functional attribute and has a corresponding axis variable;

providing one or more logic expressions that evaluate whether the design has achieved one or more of said functional states, said logic expressions set each one of said n axis variables to an integer value corresponding to said functional state when said logic expressions evaluate true;

providing a grid declaration that converts said n axis variables to an integer that is a unique linear index value that corresponds to the cross-product of said functional states achieved by the design by multiplying the integer value of each said axis variable except the nth said axis variable by the product of the sizes of each higher-order axis than the axis to which said axis variable corresponds, summing the results, and adding the integer value of the nth said axis variable, said grid declaration also records a hit and maintains a map of hits at each linear index value determined during a simulation, and downloads said map to a database; and

Appl. Serial No. 09/966,049
Amendment Dated November 11, 2005
Reply to Office Action of July 25, 2005

31876-0263

providing a parser that translates said monitor declaration, said axis declarations, said logic expressions, and said grid declaration into a computer program comprising a higher-order software language, said parser further translates each said unique linear index value to a character string comprising a concatenation of character strings that correlate to said grid name and to each said functional state within said cross-product achieved by the design.

Claim 13 (Currently Amended)

A method that monitors a design simulation using a grid to support design verification coverage analysis, comprising:

declaring a monitor in a monitor declaration that provides a unique name for the grid;

declaring n ordered axes using axis declarations, wherein n is at least 1, each said axis declaration names an axis comprising a first axis through a n th axis, wherein each said axis corresponds to a functional attribute of the design and has an axis size that comprises two or more functional states of said functional attribute and has a corresponding axis variable;

evaluating one or more logic expressions to determine whether the design has achieved one or more of said functional states;

setting each one of said n axis variables to an integer value corresponding to said functional state when said logic expressions evaluate true;

Appl. Serial No. 09/966,049
Amendment Dated November 11, 2005
Reply to Office Action of July 25, 2005

31876-0263

using a grid declaration that converts said n axis variables to an integer that is a unique linear index value that corresponds to the cross-product of said functional states achieved by the design by multiplying the integer value of each said axis variable except the nth said axis variable by the product of the sizes of each higher-order axis than the axis to which said axis variable corresponds, summing the results, and adding the integer value of the nth said axis variable, said grid declaration also records a hit and maintains a map of hits at each linear index value determined during a simulation, and downloads said map to a database; and

translating said monitor declaration, said axis declarations, said logic expressions, and said grid declaration into a computer program comprising a higher-order software language, and translating each said unique linear index value to a character string comprising a concatenation of character strings that correlate to said grid name and to each said functional state within said cross-product achieved by the design.

Claim 14 (Currently Amended)

A program storage device readable by a machine, tangibly embodying a program of instructions executable by the machine to perform a method that monitors a design simulation using a grid to support design verification coverage analysis, comprising:

declaring a monitor in a monitor declaration that provides a unique name for the grid;

Appl. Serial No. 09/966,049
Amendment Dated November 11, 2005
Reply to Office Action of July 25, 2005

31876-0263

declaring n ordered axes using axis declarations, wherein n is at least 1, each said axis declaration names an axis comprising a first axis through a n th axis, wherein each said axis corresponds to a functional attribute of the design and has an axis size that comprises two or more functional states of said functional attribute and has a corresponding axis variable;

evaluating one or more logic expressions to determine whether the design has achieved one or more of said functional states;

setting each one of said n axis variables to an integer value corresponding to said functional state when said logic expressions evaluate true;

using a grid declaration that converts said n axis variables to an integer that is a unique linear index value that corresponds to the cross-product of said functional states achieved by the design by multiplying the integer value of each said axis variable except the n th said axis variable by the product of the sizes of each higher-order axis than the axis to which said axis variable corresponds, summing the results, and adding the integer value of the n th said axis variable, said grid declaration also records a hit and maintains a map of hits at each linear index value determined during a simulation, and downloads said map to a database; and

Appl. Serial No. 09/966,049
Amendment Dated November 11, 2005
Reply to Office Action of July 25, 2005

31876-0263

translating said monitor declaration, said axis declarations, said logic expressions, and said grid declaration into a computer program comprising a higher-order software language, and translating each said unique linear index value to a character string comprising a concatenation of character strings that correlate to said grid name and to each said functional state within said cross-product achieved by the design.